

Technical data cooker hoods

	Island cooker hoods					
	IKDUP 9950.0	IKDU 9900.0	EDD 9950.0	EDL 12700.0	IKD 9980.0	IKD 9885.0
Design models						
Stainless steel						
Glass + stainless steel	■		■	■	■	■
Black Chrome	■					
Platinum White		■				

Features

Sensor touch control	■		■		■	■
High-power setting	■	■	■	■	■	■
Automatic delay stop	■	■	■	■	■	■
Number of halogen lamps / power in watts		4 x 20		4 x 20		
Low-energy fluorescent lamps / power in watts						
Number of worktop lamps / power in watts						
LED / power in watts	4 x 5		3		4 x 5	4 x 5
LED glass / power in watts					2 x 2	
No touch system			■		■	
Night light system					■	
Digital display	■		■		■	■
Rim suction	■		■	■	■	■
Fume sensor						
Remote control optional	■		■	■	■	■
Filter saturation indicator grease filter / charcoal filter	■ / ■	■ / ■	■ / ■	■ / ■	■ / ■	■ / ■
Number of metal grease filters	2	2	2	1	3	2

Technical data

Extraction rate in m³/h (to the outside) min. / dB	305 / 30	350/47	305 / 30	350/47	305 / 30	305/30
max. / dB	520 / 45	825/58	520 / 45	620/58	520 / 45	520/45
int. / dB	800/56	950/63	800/56	800/69	800/56	800/56
Connected load in watts	235	340	218	340	237	235
Voltage in V	220 - 240	~230	220 - 240	~230	220 - 240	220 - 240
Frequency in Hz	50 - 60	50	50 - 60	50	50 - 60	50 - 60
Length of connection cable in metres, approx.	1	1	1	1	1	1
Minimal clearance above electric hobs	650	650		650	650	650
Minimal clearance above gas hobs	750	750		750	750	750
Extraction air connection diameter in mm	150	150	150	150	150	150

Dimensions (appliance dimensions in mm)

Width	898	Ø 900	898	1200	898	900
Height min.	450	450*	860	250	900	820
Height max.		**	1,210		1,240	1,020
Depth	450		364	600	530	660

Possible dimensions for custom-built models (see pages 227-229)

Height max.	—	—	—	—	1,580	1,270
Height min.	—	—	—	—	900	700
Height min. recirculating air mode	—	—	—	—	900	800

* Height of canopy ** Total height see product description

Technical data cooker hoods

	Island cooker hoods					
	IKD 9380.1	IKD 12440.0	IKD 9440.0	IKD 9210.0	IKD 3850.0	IKD 4850.0
Design models						
Stainless steel		■	■		■	■
Glass + stainless steel	■			■		■
Black Chrome						
Platinum White						

Features

Sensor touch control					■	■
High-power setting	■	■	■	■	■	■
Automatic delay stop	■	■	■	■	■	■
Number of halogen lamps / power in watts				4 x 20		
Low-energy fluorescent lamps / power in watts						
Number of worktop lamps / power in watts	4 x 9					
LED / power in watts		4 x 5	4 x 5		4 x 5	2 x 5
LED glass / power in watts						
No touch system						
Night light system						
Digital display		■	■		■	■
Rim suction					■	■
Fume sensor						
Remote control optional					■	■
Filter saturation indicator grease filter / charcoal filter		■ / ■	■ / ■		■ / ■	■ / ■
Number of metal grease filters	2	4	4	3	1	1

Technical data

Extraction rate in m³/h (to the outside) min. / dB	240/28	305/30	305/30	240/28	305/30	305/30
max. / dB	470/45	520/45	520/45	470/45	520/45	520/45
int. / dB	780/57	800/56	800/56	780/57	800/56	800/56
Connected load in watts	286	235	235	290	235	225
Voltage in V	~220	220 - 240	220 - 240	~220	220 - 240	220 - 240
Frequency in Hz	50	50 - 60	50 - 60	50	50 - 60	50
Length of connection cable in metres, approx.	1	1	1	1	1	1
Minimal clearance above electric hobs	650	650	650	500	650	650
Minimal clearance above gas hobs	750	750	750	650	750	750
Extraction air connection diameter in mm	150	150	150	150	150	150

Dimensions (appliance dimensions in mm)

Width	900	1,200	900	900	380	490
Height min.	810	750	750	817	750	735
Height max.	1,110	970	970	1,117	980	880
Depth	600	660	660	600	380	490

Possible dimensions for custom-built models (see pages 227-229)

Height max.	1,110	1,220	1,220	1,117	1,180	1,180
Height min.	500	680	680	600	650	650
Height min. recirculating air mode	650	750	750	650	700	700

* Height of canopy ** Total height see product description

Technical data cooker hoods

	Chimney cooker hoods					
	KD 9540.0	KD 9970.0	KD 9960.0	KD 9580.0	KD 7580.0	KD 9570.0
Design models						
Stainless steel						
Glass + stainless steel		■	■	■	■	
Design Jet-black						■
Black Chrome						■
Platinum White	■					

Features

Sensor touch control		■	■	■	■	■
High-power setting	■	■	■	■	■	■
Automatic delay stop	■	■	■	■	■	■
Number of halogen lamps / power in watts	3 x 20					2 x 20
Low-energy fluorescent lamps / power in watts						
Number of worktop lamps / power in watts						
LED / power in watts		3 x 5	2 x 5	2 x 5	2 x 5	
LED glass / power in watts						
No touch system						
Night light system						
Digital display		■	■	■	■	■
Rim suction	■	■	■	■	■	■
Fume sensor						
Remote control optional		■	■	■	■	
Filter saturation indicator grease filter / charcoal filter	■ / ■	■ / ■	■ / ■	■ / ■	■ / ■	■ / ■
Number of metal grease filters	1	2	2	1	1	1

Technical data

Extraction rate in m³/h (to the outside)	min. / dB	300/35	305/30	305/30	305/30	305/30	240/41
	max. / dB	600/52	520/45	520/45	520/45	520/45	470/58
	int. / dB	700/56	800/56	800/56	800/56	800/56	780/70
Connected load in watts		310	230	225	225	225	290
Voltage in V		230 - 240	220 - 240	220 - 240	220 - 240	220 - 240	~220
Frequency in Hz		50	50 - 60	50 - 60	50 - 60	50 - 60	50
Length of connection cable in metres, approx.		1	1	1	1	1	1
Minimal clearance above electric hobs		650	400	400	400	400	300
Minimal clearance above gas hobs		750	550	550	550	550	300
Extraction air connection diameter in mm		150	150	150	150	150	150

Dimensions (appliance dimensions in mm)

Width	900	890	898	898	698	900
Height min.	847	1,050	955	810	810	608*
Height max.	991	1,330	1,235	1,090	1,090	1,070 - 1,400**
Depth	433	500	470	420	420	537

Possible dimensions for custom-built models (see pages 227-229)

Height max.	1650	1,600	1,530	1,390	1,390	—
Height min.	600	1,050	955	750	750	—
Height min. recirculating air mode	650	1,050	955	800	800	—

* Height of canopy ** Total height see product description

Technical data cooker hoods

	Chimney cooker hoods					
	KD 9885.0	KD 9980.0	KD 12440.0	KD 9440.0	KD 9210.0	KD 6210.0
Design models						
Stainless steel			■	■		
Glass + stainless steel	■	■			■	■
Design Jet-black						
Black Chrome						
Platinum White						

Features

Sensor touch control	■	■				
High-power setting	■	■	■	■	■	■
Automatic delay stop	■	■	■	■	■	■
Number of halogen lamps / power in watts					2 x 20	2 x 20
Low-energy fluorescent lamps / power in watts						
Number of worktop lamps / power in watts						
LED / power in watts	3 x 5	2 x 5	3 x 5	3 x 5		
LED glass / power in watts		2 x 2				
No touch system		■				
Night light system		■				
Digital display	■	■	■	■		
Rim suction	■	■				
Fume sensor						
Remote control optional	■	■				
Filter saturation indicator grease filter / charcoal filter	■ / ■	■ / ■	■ / ■	■ / ■		
Number of metal grease filters	2	2	4	3	3	2

Technical data

Extraction rate in m³/h (to the outside)	min. / dB	305 / 30	305 / 30	305 / 30	305 / 30	240/28	240/28
	max. / dB	520/45	520 / 45	520/45	520/45	470/45	470/45
	int. / dB	800/56	800/56	800/56	800/56	780/57	780/57
Connected load in watts		230	237	230	230	290	290
Voltage in V		220 - 240	220 - 240	220 - 240	220 - 240	~220	~220
Frequency in Hz		50 - 60	50 - 60	50 - 60	50 - 60	50	50
Length of connection cable in metres, approx.		1	1	1	1	1	1
Minimal clearance above electric hobs		650	650	650	650	500	500
Minimal clearance above gas hobs		750	750	750	750	650	650
Extraction air connection diameter in mm		150	150	150	150	150	150

Dimensions (appliance dimensions in mm)

Width	900	898	1,200	900	900	600
Height min.	680	940	630	630	687	687
Height max.	1,270	1,220	1,220	1,220	1,017	1,017
Depth	500	400	500	500	480	480

Possible dimensions for custom-built models (see pages 227-229)

Height max.	1,650	1,520	1,600	1,600	1,017	1,017
Height min.	650	750	600	600	650	650
Height min. recirculating air mode	750	850	720	720	650	650

* Height of canopy ** Total height see product description

Technical data cooker hoods

	Chimney cooker hoods			
	KD 9380.1	KD 8380.1	KD 7380.1	KD 6380.1
Design models				
Stainless steel				
Glass + stainless steel	■	■	■	■
Design Jet-black				
Black Chrome				
Platinum White				

Features

Sensor touch control				
High-power setting	■	■	■	■
Automatic delay stop	■	■	■	■
Number of halogen lamps / power in watts				
Low-energy fluorescent lamps / power in watts				
Number of worktop lamps / power in watts	2 x 9	2 x 9	2 x 9	2 x 9
LED / power in watts				
LED glass / power in watts				
No touch system				
Night light system				
Digital display				
Rim suction				
Fume sensor				
Remote control optional				
Filter saturation indicator grease filter / charcoal filter				
Number of metal grease filters	2	1	1	1

Technical data

Extraction rate in m³/h (to the outside)	min. / dB	240/28	240/28	240/28	240/28
	max. / dB	470/45	470/45	470/45	470/45
	int. / dB	780/57	780/57	780/57	780/57
Connected load in watts		268	268	268	268
Voltage in V		~220	~220	~220	~220
Frequency in Hz		50	50	50	50
Length of connection cable in metres, approx.		1	1	1	1
Minimal clearance above electric hobs		650	650	650	650
Minimal clearance above gas hobs		750	750	750	750
Extraction air connection diameter in mm		150	150	150	150

Dimensions (appliance dimensions in mm)

Width	898	798	698	598
Height min.	750	750	750	750
Height max.	1,010	1,010	1,010	1,010
Depth	500	500	500	500

Possible dimensions for custom-built models (see pages 227-229)

Height max.	1,010	1,010	1,010	1,010
Height min.	650	650	650	650
Height min. recirculating air mode	650	650	650	650

* Height of canopy ** Total height see product description

Technical data cooker hoods

	Built-in telescopic slimline hoods						
	EDIP 9650.0	EDIP 6650.0	EDIP 9550.0	EDIP 6550.0	EDIP 938.1	EDIP 638.1	EDIP 6400.1
Design models							
Stainless steel	■	■	■	■	■	■	■
Glass + stainless steel							
Black Chrome							
Platinum White							

Features

Sensor touch control							
High-power setting	■	■	■	■			
Automatic delay stop			■	■			
Number of halogen lamps / power in watts	2 x 20	2 x 20	3 x 20	2 x 20			2 x 20
Low-energy fluorescent lamps / power in watts					2 x 9	2 x 9	
Number of worktop lamps / power in watts							
Digital display							
Rim suction							
Fume sensor							
Remote control optional							
Filter saturation indicator grease filter / charcoal filter							
Number of metal grease filters	1	1	2	2	4	2	2

Technical data

Extraction rate in m³/h (to the outside)	min. / dB	230/46	230/46	150/36	150/36	280/51	280/51	
	max. / dB	480/61	480/61	450/53	450/53	550/65	550/65	605/64
	int. / dB	630/66	630/66	580/56	580/56			
Connected load in watts		180	180	280	280	158	158	290
Voltage in V		220 - 240	220 - 240	~230	~230	220 - 240	220 - 240	~230
Frequency in Hz		50	50	50	50	50	50	50
Length of connection cable in metres, approx.		1	1	1	1	1	1	1
Minimal clearance above electric hobs		650	650	600*	600*	450*	450*	600*
Minimal clearance above gas hobs		650	650	650*	650*	650*	650*	650*
Extraction air connection diameter in mm		150	150	125*	125*	150*	150*	125*

Dimensions (appliance dimensions in mm)

Width	898	598	900	600	900	600	600
Height min.	465	465	343	343	465	465	184
Height max.							
Depth	280 - 435	280 - 435	300 - 490	300 - 490	270 - 411	270 - 411	300 - 490

* Special dimensions (Please ignore dimensions indicated in the users instructions)

Technical data cooker hoods

	Built-in canopy cooker hoods			
	LB 8700.0	LB 6700.0	LB 835.1	LB 635.1
Design models				
Stainless steel	■	■	■	■
Glass + stainless steel				
Black Chrome				
Platinum White				

Features

Sensor touch control				
High-power setting	■	■		
Automatic delay stop				
Number of halogen lamps / power in watts	2 x 20	2 x 20	2 x 20	2 x 20
Low-energy fluorescent lamps / power in watts				
Number of worktop lamps / power in watts				
Graphics display				
Rim suction	■	■		
Fume sensor	■	■		
Remote control optional				
Filter saturation indicator grease filter / charcoal filter	■ / ■	■ / ■	■ / –	■ / –
Number of metal grease filters	1	1	1	1

Technical data

Extraction rate in m³/h (to the outside) min. / dB	300/38	300/38	260/33	260/33
max. / dB	565/55	565/55	490/48	490/48
int. / dB	650/58	650/58	700/53	700/53
Connected load in watts	190	190	190	190
Voltage in V	220 - 240	220 - 240	220 - 240	220 - 240
Frequency in Hz	50	50	50	50
Length of connection cable in metres, approx.	0.8	0.8	0.8	0.8
Minimal clearance above electric hobs	650	650	650	650
Minimal clearance above gas hobs	650	650	650	650
Extraction air connection diameter in mm	150	150	150	150

Dimensions (appliance dimensions in mm)

Width	718	539	700	520
Height min.	284	284	245	245
Height max.				
Depth	284	284	285	285